

Lighting Your Life Since 1970

Product Specifications - 23071CLFTPC		
Job Name:	Job Type:	
Quantity:	Comments	



23071CLFTPC

Silo 1-Light Wall Sconce

Finish Polished Chrome

Lamping Number of Bulbs

rumber of Buibe	•
Light Type	Xenon
Bulb Type	G9 Frost
Max Bulb Wattage	75
Max Fixture Wattage	75
Rated Life	±2,000 Hours
Rated Lumens	±1,300
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A

Glass/Shade
Clear/Frosted

Measurements	
Width	5.00"
Height	7.50"
Length	N/A
Extension	5"
Back Plate Width	5.00"
Back Plate Height	7.48"
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.43 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A

Product Category Wall Sconce

	Shipping	
"	Carton Weight	2.43 lbs
"	Carton Width	10'
١	Carton Height	8'
"	Carton Length	10'
"	Carton Cubic Feet	0.45
"	Master Pack	1
١	Master Pack Weight	N/A
٨	Master Pack Width	N/A
١	Master Pack Height	N/A
3	Master Pack Length	N/A
١	Master Cubic Feet	N/A
١	UPS Shippable	Yes

Cei	tit	ıcai	101	1

Dimmable

Ballast/Driver/Transformer

Safety Rating	Damp
Energy Star	No :
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

<i>r</i> 1	•	h	Δ	r
v	u	ш	C	

Canopy Height Canopy Length

No

Standard

Other	
UPC Code	783209086760
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Metal

Equivalents

N/A

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.