Specifications		Model number
Energy Consumption: Number of LEDs: LED Rated Lifespan: Color Temperature (Typical) – Cool: Color Temperature (Typical) – Warm: Color Rendering Index (CRI): Dimmer: Brightness Adjustability: Standard Color Finish*:	10.5 watts 42 LEDs 50,000 hours 4,500 K 3,500 K 85 Built-in touchstrip Multiple dimming levels Metallic Black, Silver	AR3000 C** = Cool White Light W** = Warm White Light MBK = Metallic Black SIL = Silver
Material: Cord Color: Cord Length:	Aluminum/Plastic Black 10'	← DSK = Desk Base ← CLP = Clamp (One-Piece)
Transformer (100–240 V; 50/60 Hz): Included – C-UL-US Certified *Custom colors are available at additional cost. Contact Koncept or your sales representative for a quote.		

Dimensions Accessories (*optional) 15.13 16 15 180 Desk base Slatwall mount Wall mount Grommet mount 2.6" 360° (MT-02-D001) (MT01S2) (MT01W1) (MT-01-G001) 16.42″ 180° 130 (90° forward Clamp (one-piece) Through-table mount Occupancy sensor* Two-piece clamp (MT-01-C004) (MT01C3) (MT01T1) (P7-01-OCC01A)

LEED credit eligibility

Energy & Atmosphere (EA) Credit 1.1: Optimize Energy Performance LED lighting to reduce energy consumption. (Potential points: 3)

Innovation In Design (ID) Credit 1.1-1.4: Innovation in Design Z-Bar® features the original three-bar design for maximum reach and flexibility. The LED head can spin in its socket, sweep side to side, and rotate around the end of the arm to point in any direction. The lamp also features a built-in touchstrip for brightness adjustability.

Materials & Resources (MR)

(Potential points: 4)

Credit 4.1: Recycled Content - 10% Lamps contain parts made out of 10% pre-consumer recycled content. (Potential points: 1) Credit 4.2: Recycled Content - 20% Lamps contain parts made out of 20% pre-consumer recycled content. (Potential points: 2)


Environmental considerations

Lamp contains 38% preconsumer recycled material by weight* Aluminum housing is fully recyclable All color finishes use water-based paint All cardboard used in packaging is FSC certified LEDs do not contain mercury

*in standard configuration (includes transformer and weighted base)

Photometrics

Light source placed at 15" away from worksurface



(Shown: photometrics of diffused light model)

GRM = Grommet Mount THR = Through-Table Mount **For diffused light, use "CD" for cool diffused light and

"WD" for warm diffused light.