


**12V LED/INCANDESCENT DECK & PATIO**

**FULL BACK  
MINI DECK**



**15045 AZT**

**MINI DECK**



**15165 AZ**

**SOLID BRASS DECK**



**15477 CBR**

Ordering Guide & Finish	15045 AZT	15165 AZ	15477 CBR																																																																
Housing	Cast Aluminum	Durable thermoplastic composite resin, one-piece construction. Extremely resistant to impact, weather and the effects of UV.	Cast Brass																																																																
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket	12V T5 wedge base socket																																																																
Supplied Lamp	6.5-W(VA) 918X (17022) Xenon light source Power usage at 12V AC input VA MAX: 6.5-W(VA)	6.5-W(VA) 918X (17023) Xenon light source Power usage at 12V AC input VA MAX: 6.5-W(VA)	Lamp not supplied unless noted																																																																
Incandescent Lamp Options	4-W(VA) 901X (17021)	4-W(VA) 901X (17021)	12V AC/DC input. Max:13W (VA) Type 912. See page 140.																																																																
LED Lamp Options	2W (18039-18041) see page 137 Compares up to 16W Xenon Light distribution may be affected by location of sockets	2W (18039-18041) see page 137 Compares up to 16W Xenon Light distribution may be affected by location of sockets	2W T5 Side mount wedge base (18120-18121) see page 138 Compares up to 16W Xenon.																																																																
Wiring	72" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	71" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	73" of usable #18-2, SPT-1-W leads. Cable connectors not included.																																																																
Mounting Access. (Included)	N/A	Stainless Steel surface mounting bracket	Mounting hardware included 2 #8 screws																																																																
Matching Outdoor Path Lights	15005, 15011, 15315, 15326, 15328																																																																		
Notes	N/A	N/A	Brass will develop natural patina over time																																																																
Photometric with Supplied Lamp	<table border="1"> <thead> <tr> <th>Mounting Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> </tr> </thead> <tbody> <tr> <td>6'</td> <td>2.8</td> <td>.06</td> <td>.03</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>12'</td> <td>4.1</td> <td>.73</td> <td>.15</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>30'</td> <td>1.7</td> <td>.87</td> <td>.37</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Mounting Height	1'	2'	3'	4'	5'	6'	7'	6'	2.8	.06	.03	-	-	-	-	12'	4.1	.73	.15	-	-	-	-	30'	1.7	.87	.37	.1	-	-	-	<table border="1"> <thead> <tr> <th>Mounting Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> </tr> </thead> <tbody> <tr> <td>6'</td> <td>1.9</td> <td>0.3</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>12'</td> <td>2.4</td> <td>.4</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>30'</td> <td>.9</td> <td>.4</td> <td>.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Mounting Height	1'	2'	3'	4'	5'	6'	7'	6'	1.9	0.3	-	-	-	-	-	12'	2.4	.4	-	-	-	-	-	30'	.9	.4	.2	-	-	-	-	
Mounting Height	1'	2'	3'	4'	5'	6'	7'																																																												
6'	2.8	.06	.03	-	-	-	-																																																												
12'	4.1	.73	.15	-	-	-	-																																																												
30'	1.7	.87	.37	.1	-	-	-																																																												
Mounting Height	1'	2'	3'	4'	5'	6'	7'																																																												
6'	1.9	0.3	-	-	-	-	-																																																												
12'	2.4	.4	-	-	-	-	-																																																												
30'	.9	.4	.2	-	-	-	-																																																												