

SOLID BRASS  
MISSIONARY



**15480 CBR**

SOLID BRASS  
TRADITIONAL



**15478 CBR**

Ordering Guide & Finish	15480 CBR	15478 CBR
Housing	Cast Brass	Cast Brass
Lamp Base	12V bi-pin, high temperature porcelain socket with glass dome	12V bi-pin, high temperature porcelain socket with glass dome
Supplied Lamp	Lamp not supplied unless noted	Lamp not supplied unless noted
Incandescent Lamp Options	12V AC input Max: 20W(VA) T-3. See Page 140.	12V AC input Max: 20W(VA) T-3. See Page 140.
LED Lamp Options	2W G4/T3 Bi-Pin (18042-18044) See page 137. Compares to 20W Halogen.	2W G4/T3 Bi-Pin (18042-18044) See page 137. Compares to 20W Halogen.
Wiring	30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	30" of usable #18-2, SPT-1-W leads. Cable connectors not included.
Mounting Access. (Included)	8" In-ground stake	8" In-ground stake
Optional Accessories	N/A	N/A
Notes	Optimized for LED fit & lamp performance. Brass will naturally patina over time.	Optimized for LED fit & lamp performance. Brass will naturally patina over time.