

# 12V LED DECK & PATIO

## MINI DECK LIGHT



## HALF MOON



### 15765 AZT, BBR, BKT, WHT

### 15764 AZT, BBR, WHT

Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White												
Ordering Guide & Finish	15765 AZT27R 15765 BBR27R 15765 BKT27R 15765 WHT27R	15765 AZT30R 15765 BBR30R 15765 BKT30R 15765 WHT30R	15764 AZT27R 15764 BBR27R 15764 WHT27R	15764 AZT30R 15764 BBR30R 15764 WHT30R												
Housing	Cast Aluminum or Cast Brass		Aluminum or Cast Brass with satin-etched lens													
Light Source	1 Integrated High Output Cree® LEDs, tightly binned for color uniformity, and constant current driver		1 Integrated High Output Cree® LED, tightly binned for color uniformity, and constant current driver													
Color Temp. (CCT) & CRI	2700K (-50/+100) / 80s CRI 3000K (-45/+130) / 80s CRI		2700K (-50/+100) / 80s CRI 3000K (-45/+130) / 80s CRI													
Power Usage at 12V AC Input VA and Watts	.86 W, 1.86 VA		.86 W, 1.86 VA													
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology													
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours													
Delivered Lumens & Efficacy	2700K = 43 Lm 2700K = 51 Lm/W	3000K = 41 Lm 3000K = 50 Lm/W	2700K = 43 Lm 2700K = 51 Lm/W	3000K = 41 Lm 3000K = 50 Lm/W												
Wiring	72" of usable #18-2, SPT-1-W leads. Cable Connectors supplied. WHT has coordinating white leads.		72" of usable #18-2, SPT-1-W leads. Cable Connectors supplied. WHT has coordinating white leads.													
Mounting Access. (Included)	Stainless steel mounting bracket and hardware		Stainless steel mounting bracket and hardware													
Notes	Versatile mini size. Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.		Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.													
Fixture Photometric (fc)*	Mounting Light	0'	.5'	1'	2'	3'	4'	5'	Mounting Light	0'	.5'	1'	2'	3'	4'	5'
	6"	76.50	20.00	3.00	0.20	0.06	0.05	0.03	29.70	14.80	1.60	0.07	0.05	0.01	0.01	0.00
	12"	13.00	10.63	4.80	1.10	0.20	0.08	0.05	8.30	6.40	2.60	0.45	0.08	0.02	0.01	
	30"	3.20	3.40	2.60	1.20	0.52	0.24	0.12	2.10	2.05	1.55	0.50	0.30	0.11	0.09	

\*Values stated for 3000K. -10% for 2700K.