

# 12V LED DECK & PATIO

## MINI DECK LIGHT



## HALF MOON



### 15765 AZT, BBR, BKT, WHT

### 15764 AZT, BBR, WHT

Kelvin	2700K – Warm White		3000K – Pure White		2700K – Warm White		3000K – Pure White	
Ordering Guide & Finish	15765 AZT27R 15765 BBR27R 15765 BKT27R 15765 WHT27R		15765 AZT30R 15765 BBR30R 15765 BKT30R 15765 WHT30R		15764 AZT27R 15764 BBR27R 15764 WHT27R		15764 AZT30R 15764 BBR30R 15764 WHT30R	
Housing	Cast Aluminum or Cast Brass				Aluminum or Cast Brass with satin-etched lens			
Light Source	1 Integrated High Output Cree® LEDs, tightly binned for color uniformity, and constant current driver				1 Integrated High Output Cree® LED, tightly binned for color uniformity, and constant current driver			
Color Temp. (CCT) & CRI	2700K (-50/+100) / 80s CRI 3000K (-45/+130) / 80s CRI				2700K (-50/+100) / 80s CRI 3000K (-45/+130) / 80s CRI			
Power Usage at 12V AC Input VA and Watts	.86 W, 1.86 VA				.86 W, 1.86 VA			
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology				9V-15V AC/DC with no loss in output due to constant current technology			
Lumen Maint.	Tested to an L-70 of 40,000 hours				Tested to an L-70 of 40,000 hours			
Delivered Lumens & Efficacy	2700K = 43 Lm 2700K = 51 Lm/W		3000K = 41 Lm 3000K = 50 Lm/W		2700K = 43 Lm 2700K = 51 Lm/W		3000K = 41 Lm 3000K = 50 Lm/W	
Wiring	72" of usable #18-2, SPT-1-W leads. Cable Connectors supplied. WHT has coordinating white leads.				72" of usable #18-2, SPT-1-W leads. Cable Connectors supplied. WHT has coordinating white leads.			
Mounting Access. (Included)	Stainless steel mounting bracket and hardware				Stainless steel mounting bracket and hardware			
Notes	Versatile mini size. Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.				Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.			
Fixture Photometric (fc)*	Mounting Light	0'	.5'	1'	2'	3'	4'	5'
	6"	76.50	20.00	3.00	0.20	0.06	0.05	0.03
	12"	13.00	10.63	4.80	1.10	0.20	0.08	0.05
	30"	3.20	3.40	2.60	1.20	0.52	0.24	0.12

\*Values stated for 3000K. -10% for 2700K.