

SIDE MOUNT CAST BRASS



15827 BBR

CENTER MOUNT



15826 AZT, BKT

Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White						
Ordering Guide & Finish	15827 BBR27R	15827 BBR30R	15826 AZT27R 15826 BKT27R	15826 AZT30R 15826 BKT30R						
Housing	Cast Brass		Cast Aluminum							
Light Source	8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver		8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver							
Color Temp. (CCT) & CRI	2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI		2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI							
Power Usage at 12V AC Input VA and Watts	4.3 W, 5.8 VA		4.3 W, 5.8 VA							
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology							
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours							
Delivered Lumens & Efficacy	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm/W 3000K = 73 Lm/W	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm 3000K = 73 Lm/W						
Wiring	53" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		50" of usable #18-2, SPT-1-W leads. Cable connectors supplied.							
Mounting Access. (Included)	8" slotted in-ground stake		8" slotted in-ground stake Black/White Deflector							
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket FM127265 – Hexcell Louver							
Optional Lens Accessories	15677 CLR – Sprinkler Shield		N/A							
Incandescent	N/A		15326 – on page 113							
Notes	Coordinates with matching LED deck light 15765 on page 54		Coordinates with matching LED deck light 15765 on page 54							
Fixture Photometric (fc)*	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
	Footcandles	92.00	27.00	5.20	1.20	0.30	0.16	0.08	0.05	0.04
	W/Black Deflector	30.30	21.10	5.30	1.50	0.50	0.19	0.10	0.05	0.04
	W/White Deflector	35.00	23.50	5.30	1.60	0.50	0.25	0.14	0.10	0.09

\*Values stated for 3000K. -10% for 2700K.