

# 12V LED PATH & SPREAD

## BROAD ROOF



**15833 AZT**

## TAPERED COLUMN



**15804 AZT**

	15833 AZT		15804 AZT																	
Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White																
Ordering Guide & Finish	15833 AZT27R	15833 ATZ30R	15804 AZT27R	15804 AZT30R																
Housing	Cast Aluminum with cast bottom driver compartment		Cast Aluminum with cast bottom driver compartment																	
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver		6 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver																	
Color Temp. (CCT) & CRI	2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI		2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI																	
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA		1 W, 1.7 VA																	
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology																	
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours																	
Delivered Lumens & Efficacy	2700K = 126 Lm 2700K = 31 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W	2700K = 126 Lm 2700K = 31 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W																
Wiring	30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.																	
Mounting Access. (Included)	8" slotted in-ground stake		8" slotted in-ground stake																	
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket																	
Incandescent	N/A		N/A																	
Fixture Photometric (fc)*	Distance from Light										Distance from Light									
	0'	1'	2'	3'	4'	5'	6'	7'	8'		0'	1'	2'	3'	4'	5'	6'	7'	8'	
Footcandles	13.5	3.7	0.8	0.3	0.2	0.1	-	-	-		7.2	3.5	1.4	0.8	0.5	0.3	-	-	-	

\*Values stated for 3000K. -10% for 2700K.