

FOUR CORNERS



16121 AZT, BKT, Tzt

OVERLAY



16122 AZT

	2700K – Warm White		3000K – Pure White							
Kelvin	2700K – Warm White		3000K – Pure White							
Ordering Guide & Finish	16121 AZT27 16121 BKT27 16121 Tzt27	16121 AZT30 16121 BKT30 16121 Tzt30	16122 AZT27	16122 AZT30						
Housing	Cast Aluminum		Aluminum							
Light Source	8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver		3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver							
Color Temp. (CCT) & CRI	2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI		2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI							
Power Usage at 12V AC Input VA and Watts	4.3 W, 5.8 VA		3.8 W, 4.95 VA							
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology							
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours							
Delivered Lumens & Efficacy	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm 3000K = 73 Lm/W	2700K = 168 Lm 2700K = 46 Lm/W	3000K = 182 Lm 3000K = 46 Lm/W						
Wiring	30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.							
Mounting Access. (Included)	8" slotted in-ground stake Black/White Deflector		8" slotted in-ground stake							
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket FM127265 – Hexcell Louver		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket							
Incandescent	N/A		N/A							
Notes	Coordinating deck light on page 55		Coordinating deck light on page 56							
Fixture Photometric (fc)*	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
	Footcandles	74.40	27.00	5.20	1.20	0.30	0.16	0.08	0.05	0.04
	W/Black Deflector	36.00	21.90	4.50	1.10	0.34	0.16	0.08	0.05	0.04
	W/White Deflector	40.50	21.50	5.00	1.30	0.50	0.26	0.15	0.11	0.10

*Values stated for 3000K. -10% for 2700K.